



Minimal Leak Path



Prefit the screw



Tighten by hand



Key Features

- 2 installation options
- Minimal Leak Path
- Quick & Easy to Install
- Non-Conductive
- 2 screw types - Wing or 8mm Hex
- 2 Material Options - Nylon 6.6. or Nylon 12
- Non-Corrosive
- Non-Magnetic
- Excellent UV resistance (PA12)



Dimensions & Part Numbers - Screw Type

HCL Part No	Minimum Diameter (A) mm / inch	Maximum Diameter (A) mm / inch	Band Width (B) mm / inch	Band Thickness (C) mm / inch	Screw Type	Max Torque
SCREW CLAMP						
PWD-13-50-SC-PA66-BK	25.0 / 1.00	50.0 / 2.00	12.7 / 0.50	3.25 / 0.13	8mm Hex	2.0Nm
PWD-13-75-SC-PA66-BK		75.0 / 3.00				
PWD-13-100-SC-PA66-BK		100.0 / 4.00				
PWD-13-125-SC-PA66-BK	50.0 / 2.00	125.0 / 5.00				
PWD-13-150-SC-PA66-BK	75.0 / 3.00	150.0 / 6.00				
PWD-13-50-SC-PA12-BK	25.0 / 1.00	50.0 / 2.00				
PWD-13-75-SC-PA12-BK		75.0 / 3.00				
PWD-13-100-SC-PA12-BK		100.0 / 4.00				
PWD-13-125-SC-PA12-BK	50.0 / 2.00	125.0 / 5.00				
PWD-13-150-SC-PA12-BK	75.0 / 3.00	150.0 / 6.00				



Dimensions & Part Numbers - Wing Type

HCL Part No	Minimum Diameter (A) mm / inch	Maximum Diameter (A) mm / inch	Band Width (B) mm / inch	Band Thickness (C) mm / inch	Screw Type	Max Torque
WING CLAMP						
PWD-13-50-WG-PA66-BK	25.0 / 1.00	50.0 / 2.00	12.7 / 0.50	3.25 / 0.13	Wing	2.0Nm
PWD-13-75-WG-PA66-BK		75.0 / 3.00				
PWD-13-100-WG-PA66-BK		100.0 / 4.00				
PWD-13-125-WG-PA66-BK	50.0 / 2.00	125.0 / 5.00				
PWD-13-150-WG-PA66-BK	75.0 / 3.00	150.0 / 6.00				
PWD-13-50-WG-PA12-BK	25.0 / 1.00	50.0 / 2.00				
PWD-13-75-WG-PA12-BK		75.0 / 3.00				
PWD-13-100-WG-PA12-BK		100.0 / 4.00				
PWD-13-125-WG-PA12-BK	50.0 / 2.00	125.0 / 5.00				
PWD-13-150-WG-PA12-BK	75.0 / 3.00	150.0 / 6.00				

